



**RESTORE™
DECK & CONCRETE CLEANER**

DESCRIPTION AND USES

RESTORE DECK & CONCRETE CLEANER™ removes tough stains from mildew, mold, algae, fungus and moss, and leaves the surface clean. Special surfactants penetrate the surface to safely and easily dissolve the toughest stains from dirt, oil, grease, bird droppings, tree sap, and acid rain. Ideal for use on new pressure treated wood to remove mill glaze and improve adhesion of coatings. Also removes gray weathering from wood, chalking, and oxidation. Recommended for wood and composite decks, fences and concrete.

Additional uses: Exterior siding (wood, vinyl, aluminium), roofing of all types (asphalt shingles, fiberglass shingles, cedar, tile) brick and cement block, masonry, driveways, walkways, walls, and gutters.

PRODUCTS

SKU	Description
51752	1-Gallon Container

PRODUCT APPLICATION

MANUAL APPLICATION

Mix ratio = 1:8 (concentrate to water). For manual Application, mix 2 cups of concentrate with 1 gallon of water to clean approximately 2,500 sq. ft. (less on rougher surfaces). Can be applied by pump up sprayer, brush or roller. Simply apply to surface, leave for 5 to 10 minutes, and wash off.

PRESSURE WASHER

Contains anti-corrosive agents to safeguard pressure washer parts (bleach can erode O-rings).

1. Rinse surrounding plants with water, before and after application.
2. Wet surface to be cleaned, prior to applying the product.
3. Place detergent application siphon tube and screen filter directly into container. Open meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer.
4. Spray at low pressure onto a wet surface.
5. On vertical surfaces, always spray from the top down.
6. Allow product to remain on the surface for 5 to 10 minutes to penetrate. Do not allow product to dry on surface.
7. Remove siphon tube from solution and rinse surface with high pressure spray thoroughly.
8. Flush siphon tube with clean water prior to storage.

NOTE: ALWAYS MIX WITH WATER WHEN APPLYING TO A HOUSE EXTERIOR.

DIRECTIONS – MILL GLAZE REMOVAL

By using as directed on pressure treated wood, you will remove mill glaze and minimize the effects of wax and water repellents that may be present in the new wood. This will greatly improve the adhesion of Restore 10X, 4X and 2X to wood decking and reduce cure time, allowing coatings to be applied sooner to new pressure treated wood.

PRODUCT APPLICATION (cont.)

MILL GLAZE REMOVAL (cont.)

1. Apply undiluted cleaner, let stand on surfaces for 5-10 minutes to penetrate.
2. Scrub surface thoroughly with a nylon brush to remove mill glaze.
3. Rinse surface clean to remove any residue and allow to dry.
4. If water still beads on the surface, repeat steps 1-3.
5. Apply Restore 10X, 4X or 2X within 7 days of this process.

IMPORTANT INFORMATION

- When using a pressure washer to clean painted surfaces, be aware that water pressure alone may remove paint, or highlight existing discoloration caused by the sun's UV rays.
- From the garden hose, rinse nearby plants with clean water.
- Always test on an inconspicuous area first.
- Any overspray can be neutralized with large volumes of water.
- Extremely soiled or mildewed surfaces may need to be scrubbed with a bristle brush, and a second application may be needed. Mildew may not be completely removed from porous surfaces.
- For best results when cleaning decks, apply by pump-up garden sprayer, leave for 5 to 10 minutes, and rinse off with water.
- For heavy oil and grease stains (such as on driveways and garage floors), pour product directly onto the stains. Allow to penetrate for 10 minutes, then follow normal application procedures.
- In case of severe oil and grease stains on porous surfaces, oil may bleed to the surface or leave a residual stain. Repeat applications may lighten stains, but not remove completely.

CONTAINS NO BLEACH OR AMMONIA

DO NOT MIX THIS PRODUCT WITH OTHER CHEMICALS. NOTE: ALWAYS MIX WITH WATER WHEN APPLYING TO A HOUSE EXTERIOR.

CAUTION: This product contains alkaline detergents. **EYE AND SKIN IRRITANT.** Do not take internally. **FIRST AID:** In case of contact with eyes or skin, flush with water for 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. Material Safety Data Sheet available. **KEEP OUT OF REACH OF CHILDREN.**

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.