

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®**  
SPECIALTY

**RUST-OLEUM® SPECIALTY**  
**VINYL SPRAYS**

**DESCRIPTION AND USES**

Rust-Oleum® Specialty Vinyl Sprays restore color on vinyl and fabrics. This coating is ideal for car and boat seats, dashboards, upholstery, luggage, furniture, sports equipment and more. Specialty Vinyl Sprays feature an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad to reduce fatigue caused by continuous spraying.

**PRODUCT**

SKU	DESCRIPTION (Aerosol)
1909830	Black
1911830	White

**PRODUCT APPLICATION**

Use outdoors or in a well ventilated area. Use when temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 10-16" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can in motion while spraying. Keep the can the same distance from the surface. Apply two or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

**DRY & RECOAT**

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 10 minutes, to handle in 1 hour and is fully dry in 24 hours. Wait at least 6 hours before sitting or using a painted object.

**CLEAN-UP**

When finished spraying, clear spray valve by turning can upside down and pushing spray button for 5 seconds. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

	<b>TECHNICAL DATA</b>	<b>SPC-16</b>
<small>• TRUSTED QUALITY SINCE 1921 •</small> <b>RUST-OLEUM®</b> <b>SPECIALTY</b>	<b>RUST-OLEUM® SPECIALTY</b> <b>VINYL SPRAYS</b>	

**PHYSICAL PROPERTIES**

		VINYL SPRAYS
<b>Resin Type</b>		Acrylic Lacquer
<b>Pigment Type</b>		Proprietary
<b>Solvents</b>		Acetone, Toluene, Xylene
<b>MIR</b>		1.45 Max
<b>Fill Weight</b>		11 ounces
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		Approximately 7 sq.ft./can (0.65 m <sup>2</sup> /can)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	10 minutes
	<b>Handle</b>	1 hour
	<b>Recoat</b>	Anytime
<b>Dry Heat Resistance</b>		200°F (93°C)
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		-156°F (-104°C)
<b>Safety Information</b>		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.