



**STOPS RUST®  
RUST INHIBITOR SPRAY**

**DESCRIPTION AND USES**

Rust-Oleum® Rust Inhibitor is a clear coating that protects untreated, bare metal surfaces against moisture and other corrosive elements. It is suitable for use on garden tools, bicycles, metal sporting equipment, lawn equipment, iron railings and other metal surfaces.

**PRODUCTS**

SKU (10.25 fl. oz.)	Description
224284	Rust Inhibitor

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove all loose rust, scale, and previous coatings with a wire brush, scraper, or Rust-Oleum Rust Stripper.

**WARNING!** If you scrape, sand or remove old paint from any surface, you may release lead paint dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE; ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)

**PRODUCT APPLICATION (cont.)**

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area such as an open garage. Apply when temperature is between 50-90°F (10-32°C) and humidity is below 85% to ensure efficient use of the product. Do not apply to an area that, when heated, will exceed 120°F (49°C). Avoid spraying in windy, dusty conditions. Cover surrounding area to protect from spray mist.

**APPLICATION**

Shake can well before using and often during use. Hold can upright 12-16" from the surface and apply a light, thin, even coat to cover the surface. Additional coats provide increased protection. Wipe off excess with a clean cloth if the coating is too heavy. Re-apply every 1-2 years for indoor uses and every 6 months for outdoor uses.

**PAINTING**

If surfaces are to be painted in the future, remove Rust Inhibitor from the surface with a solvent such as acetone or mineral spirits prior to painting.

**PHYSICAL PROPERTIES**

	<b>RUST INHIBITOR</b>
<b>Composition</b>	Petroleum Distillates
<b>Fill Weight</b>	10.25 ounces
<b>VOC</b>	325 g/l
<b>Shelf Life</b>	1 year from date of manufacture
<b>Flash Point</b>	-156°F (-104°C)
<b>Safety Information</b>	For additional information, see SDS