



**STOPS RUST®  
LEAKSEAL® BRUSH**

**DESCRIPTION AND USES**

Rust-Oleum® Stops Rust® LeakSeal® Brush is an easy to use, rubberized protective utility coating designed to fill and seal small leaks and cracks. It provides a water-tight, flexible seal that prevents moisture penetration, rust and corrosion. This high-build formula is great for filling large, problematic and hard-to-reach areas.

It is suitable for use on metal, aluminum, galvanized metal, PVC, concrete, masonry, asphalt, vinyl siding and fiberglass. Not intended for water immersion.

**PRODUCTS**

SKU	Description
271791	1-Quart Black
275117	1-Pint Black
275116	1-Quart Crystal Clear
275118	1-Pint Crystal Clear
279614	1-Pint Crystal Clear

**PRODUCT APPLICATION**

**PAINTING CONDITIONS**

Use outdoors or in a well ventilated area indoors. Use when temperature is between 50-85°F (10-29°C) and humidity is below 85% to ensure proper drying. Do not use on objects that may exceed 200°F (93°C) surface temperature.

**SURFACE PREPARATION**

Remove dirt and debris from the area to be coated. If necessary, clean area with soap and water, rinse and let dry. All surfaces must be dry at time of application.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Stir product slowly and carefully. DO NOT shake the product. If thinning is necessary, thin the material with mineral spirits up to 10%. Use a high quality brush and dip slowly into the can (to avoid air bubbles) and apply the product with smooth, light, even strokes. Do not over brush into areas that are beginning to dry. Better results are achieved with several light coats versus one heavy coat. If applying with a roller, be sure to use a woven nap roller. Test paint in a hidden area first.

**DRY & RECOAT TIMES**

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures and higher humidity. LeakSeal Brush may be recoated when dry; between 30 minutes and 1 hour. Dries thoroughly after 24 hours.

**CLEAN-UP**

Clean brush and other tools with mineral spirits.



## TECHNICAL DATA

# STOPS RUST® LEAKSEAL® BRUSH

### PHYSICAL PROPERTIES

		LEAKSEAL BRUSH
<b>Resin Type</b>		Synthetic Rubber
<b>Pigment Type</b>		Carbon Black, Silica
<b>Solvents</b>		N-Butyl Acetate, VM&P Naphtha
<b>Weight</b>	<b>Per Gallon</b>	7.12-7.16 lbs.
	<b>Per Liter</b>	1.88-1.89 kg
<b>Solids</b>	<b>By Weight</b>	23.8-26.9%
	<b>By Volume</b>	23.4-26.0%
<b>Volatile Organic Compounds</b>		<640 g/l (5.32 lbs./gal.)
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		2-4 mils (50-100μ)
<b>Wet Film to Achieve DFT</b>		8-16 mils (200-400μ)
<b>Practical Coverage at Recommended DFT</b>		20-40 sq.ft./quart (0.5-1.0 m <sup>2</sup> /l)
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	1 hour
	<b>Recoat</b>	30 minutes to 1 hour
	<b>Fully Dry</b>	After 24 hours
<b>Shelf Life</b>		5 years
<b>Flash Point</b>		50°F (10°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.