



CABINET TRANSFORMATIONS™ WOOD REFINISHING SYSTEM

DESCRIPTION AND USES

Cabinet Transformations™ Wood Refinishing System is a long lasting rejuvenation system that brings back the original color and finish of stained wood cabinetry. It is not a stain and it will not change the color of your cabinets. Cabinet Transformations Wood Refinishing system is suitable for cabinets, vanities, interior doors, moldings and furniture. Covers up to 100 square feet or 40 linear feet.

Cabinet Transformations uses a system of a wood cleaner, color enhancer and protective topcoat to create a highly durable finish.

Tintable to one of 18 finish colors. The color appropriate kit must be tinted at the paint counter at time of purchase.

The Cabinet Transformations Wood Refinishing System kit includes both an instructional DVD and printed instructions to aid with the process and coating application. The kit also includes:

- Wood Cleaner
- Color Enhancer
- Protective Top Coat
- Cleaning Sponges
- Lint-free Cloths
- Stir Sticks

Items not supplied with the kit which need to be purchased separately:

- 2" Synthetic Paint Brushes – Premium Quality Angled or Straight
- 2" Foam Paint Brush
- 2" Smooth Painter's Tape
- 2 Buckets
- Drop Cloths
- Disposable Gloves
- Lint-Free Drying Rags or Towels

PRODUCT

SKU	DESCRIPTION (Kit)
262495	Wood Refinishing System

PRODUCT APPLICATION

Watch the entire instructional DVD and use the printed instructions for the complete, step by step, procedure on application of the materials.

IMPORTANT: Apply when air (ambient) temperature is 50-90°F (10-35°C) and relative humidity is below 60%.

SURFACE PREPARATION

To obtain best results, take cabinet doors off hinges and drawers out of frames. Remove all cabinet hardware, including hinges, drawer pulls, and knobs. The surface of the cabinets must be completely cleaned in accordance to the instructions to ensure proper performance of the Cabinet Transformations Wood Refinishing System.

APPLICATION OF WOOD CLEANER

The Cabinet Transformations Wood Cleaner prepares the surface and allows the Color Enhancer to adhere without sanding or priming. To ensure optimum results, make sure to be THOROUGH when cleaning the cabinet doors, drawers, and frames.

IMPORTANT: Your side panels of cabinets may be covered with a wood grain vinyl or paper product. If so do not apply the Wood Cleaner. Be sure to tape off these areas.

APPLICATION OF COLOR ENHANCER

The Color Enhancer will restore your cabinets' rich, original color without hiding the natural wood grain.

IMPORTANT: There is enough Color Enhancer to cover the outer cabinet frame, each drawer front, and front and back of each door with two coats. There is not enough to coat the insides of the cabinets or shelves.

APPLICATION OF THE TOPCOAT

The topcoat is formulated with self cross-linking technology that provides superior stain and scratch resistance.

IMPORTANT: The Protective Top Coat dries quickly. For best results, avoid re-brushing previously coated areas that have started to dry.

Allow to dry 12 hours before installing cabinet drawers and hardware. Allow 24 hours before full use. Avoid using cleaners on new cabinetry for 7 days.

<small>TRUSTED QUALITY SINCE 1921</small> RUST-OLEUM® Cabinet Transformations® Wood Refinishing System	TECHNICAL DATA	CAB-03
CABINET TRANSFORMATIONS™ WOOD REFINISHING SYSTEM		

PHYSICAL PROPERTIES

		CLEANER	COLOR ENHANCER	TOP COAT
Resin Type		None	Acrylic / Urethane	Acrylic / Urethane
Pigment Type		None	Titanium dioxide, mica, inerts	Titanium dioxide, mica, inerts
Solvents		Water	Water	Water
Weight	Per Gallon	8.40 lbs.	9.80-11.90 lbs.	8.47 lbs.
Solids	By Weight	4.8%	40-58%	29%
	By Volume	4.5%	30-42%	27%
Volatile Organic Compounds		<465 g/l (3.85 lbs./gal.)	<85 g/l (0.70 lbs./gal.)	<272 g/l (2.3 lbs./gal.)
Recommended Dry Film Thickness (DFT) Per Coat		n/a	2.0-2.5 mils (50-62.5µ)	4.0-8.0 mils (100-200µ)
Wet Film to Achieve DFT (unthinned material)		n/a	6.6-7.5 mils (165-187.5µ)	14.8-30.0 mils (370-750µ)
Practical Coverage at Recommended DFT (assumes 15% material loss)		n/a	160-200 sq. ft./gal. (3.9-4.7 m ² /l)	46-92 sq. ft./gal. (1.1-2.3 m ² /l)
Dry Times at 77°F (25°C) and 50% Relative Humidity	Working Time	30 minutes	30 minutes	30 minutes
	Dry to Recoat	1 hour	2-3 hours	n/a
	Full Cure	n/a	n/a	24 hours
Dry Heat Resistance		n/a	200°F (93°C)	200°F (93°C)
Shelf Life		n/a	3 years	3 years
Storage		Store in a dry area between 40-100°F (4.5-38°C)		
Safety Information		For additional information, see MSDS		

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.