



**VARATHANE®
NO SANDING REFINISHING PREP**

DESCRIPTION AND USES

Varathane® No Sanding Refinishing Prep provides an easy solution for preparing wood surfaces for refinishing without the need for sanding or use of special equipment. It prepares the wood surface by abrading and cleaning the existing worn, scratched, or dull finish without harming or discoloring the stain color underneath. No Sanding Refinishing Prep removes tough dirt and residue to leave the surface clean and ready to accept a new top coat finish. It also prepares solid wood and laminate flooring for a refinishing top coat. (Varathane Wood Refresher recommended). No mixing or dilution needed.

PRODUCTS

1-Quart	Description
247815	No Sanding Refinishing Prep

PRODUCT APPLICATION

SURFACE PREPARATION

Remove any loose dirt or dust using a damp rag. While Varathane No Sanding Refinishing Prep is compatible with all types of previously finished surfaces, it is not compatible with wax. To test the surface for wax, dampen a rag with mineral spirits and wipe it on the surface. If the rag pulls up a waxy substance, then the surface contains wax. To remove and dissolve the wax from the surface, dampen a rag with mineral spirits and wipe the surface until clean.

PRODUCT APPLICATION (cont.)

APPLICATION

Working in small sections, apply No Sanding Refinishing Prep directly to the surface with a mild abrasive scrub pad attached to a pole. Using a back and forth motion following the direction of the grain in a "Z" pattern. On vertical surface apply directly to the scrub pad and follow the procedure above. Use of glove is highly recommended.

Wipe the surface clean with a damp rag or sponge mop before the No Sanding Refinishing Prep has a chance to dry. Repeat the process until all sections of the surface have been treated and allow the entire floor to dry for 30 minutes before applying a new top coat.

Laminate Floors - No Sanding Refinishing Prep is required if you are planning to apply Varathane Wood Refresher to laminate floors.

CLEAN UP

Clean application tools and equipment with soap and water. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**TECHNICAL DATA****VARATHANE® NO SANDING REFINISHING PREP****PHYSICAL PROPERTIES**

		NO SANDING REFINISHING PREP
Resin		NA
Solvents		Glycol Ether and Water
Weight	Per Gallon	8.3 lbs.
	Per Liter	1.0 kg.
Solids	By Weight	5.2%
	By Volume	4.6%
Volatile Organic Compounds		485 g/l (4.05 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Varies with type and porosity of wood
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	30 minutes
	Topcoat	30 minutes
Shelf Life		3 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
 11 Hawthorn Parkway
 Vernon Hills, Illinois 60061
 An RPM Company

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-650
 Rev.: 011217