



# WIPE NEW® WHEELS

## DESCRIPTION AND USES

Rust-Oleum® Wipe New® Wheels provides long lasting and excellent protection against road salt, brake dust, grime and corrosion.

## FEATURES

- Protection against brake dust and corrosion
- Easy-to-use, one wipe solution
- Long lasting shine – protects through 100 car washes

## PRODUCTS

SKU	Description
WWRTLKIT	Wipe New 6PK Wheels
WWCAL	Wipe New 6PK Wheels CA Com

## PRODUCT APPLICATION

### APPLICATION CONDITIONS

Use when temperatures are between 40°F and 90°F (4°C and 32°C). Use in well ventilated and covered areas away from the sun. Do not apply Wipe New to hot surfaces or in direct sunlight. Ensure surface is clean, dry and cool to ambient temperature before applying Wipe New.

### SURFACE PREPARATION

Before opening the Wipe-It™ packet, prep all wheels intended for coating so that you can complete your Wipe New application within a few minutes after opening the packet. Once the packet is opened, the Wipe-It begins to dry. Do NOT open the Wipe-It until you are ready to use it.

Wash your wheels thoroughly with a cleansing agent and scrub brush to remove all brake dust, oils, and dirt. Rinse and inspect to ensure all dirt and stains are completely removed. Repeat as necessary until the surface is completely clean. Ensure all wheels are clean, dry, and cool to the touch before applying Wipe New.

## PRODUCT APPLICATION (cont.)

### APPLICATION

Put on the chemical resistant gloves and ensure that you are in a well ventilated area and that the wheels are completely dry. Tear open the Wipe-It packet, pull out the applicator cloth and carefully wipe the lens ONE TIME in a single wipe, from one row to the next, with a slight overlap (like mowing a lawn) until the surface is completely coated. Dab the included detail swab brush into the applicator cloth and use it to apply Wipe New into lug nut holes and other tight areas. **Tip:** Start from the tire valve stem to mark your position and work your way around the wheel until you come back to the tire valve stem. Coat the wheels on one side of the car at the same time, then open the second Wipe-It and repeat the process on the other side of the car. If Wipe New begins to dry on the applicator cloth, streaking may occur. Once the applicator cloth dries out completely, it cannot be reused and must be discarded.

If Wipe New comes in contact with an unintended surface such as paint, wipe it off immediately with a dry cloth. Within an hour of application (while still undergoing initial cure), acetone may be used to remove Wipe New from a painted surface, but not from plastic or any nonmetal surface. Because acetone can damage vehicle parts or paint, it should be used only after checking with the vehicle manufacturer or a Certified Paint Professional as to how to best apply or remove product. After Wipe New has cured, removing it will require the use of a fine polishing compound or high grit automotive sandpaper.

### DRY TIME

The wheels will dry to the touch in about 1 hour. Do not allow treated wheels to come in contact with direct moisture (rain, dew, puddles, etc) for 24 hours. Store excess product in a cool, dry place.

### COVERAGE

One Wipe-It contains enough Wipe New to treat two wheels.

### DISPOSAL

When finished, set the applicator cloth in a location out of the reach of children and allow it to dry completely prior to discarding (a few hours).



## TECHNICAL DATA

### WIPE NEW® WHEELS

## PHYSICAL PROPERTIES

		WHEELS	
Resin Type		Siloxane Polymer	
Pigment Type		NA	
Solvents		Parachlorobenzotrifluoride	California - N-Butyl Acetate, Parachlorobenzotrifluoride
Volatile Organic Compounds		None	
Practical Coverage at Recommended DFT		One Wipe-It™ contains enough Wipe New® to treat two wheels.	
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	1 hour	
	Recoat	NA	
	Full Cure	24 hours	
Shelf Life		5 years	
Flash Point		54°F (12°C)	California: 97°F (36°C)
Safety Information		For additional information, see SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.