



**READY-MIXED
POPCORN CEILING PATCH**

DESCRIPTION AND USES

Ready-Mixed Popcorn Ceiling Patch is a ready-to-use latex based product designed to repair scuffs, scars, holes and other imperfections on rough acoustic textured surfaces known as popcorn ceilings. This product is formulated to blend well with existing ceiling textures resulting in an almost invisible repair. Painting is not necessary.

PERFORMANCE CHARACTERISTICS

- Ready Mixed, easy to use
- Easy to apply
- Use to repair blemishes, scratches and scrapes
- Repair water damaged areas on popcorn ceilings
- Duplicates original finish

PRODUCTS

SKU	Description
76084	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

Area to be patched must be clean and free of all loose crumbling texture and powdery material. A putty knife is an excellent tool for removing damaged texture. If a water damaged area is to be repaired, remove texture about 1" beyond the damaged area. Prime the area with a shellac-based primer such as Zinsser B-I-N to prevent staining.

PRODUCT APPLICATION (cont.)

MIXING

Stir contents for 10 seconds. If material appears too dry, add up to 4 tablespoons of water until a paint brush dipped in the material holds product without dripping.

APPLICATION

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85%. Use a good soft bristle paint brush and dab material in place working from the outside in. The aggregate can be moved around to match the density of the original ceiling texture. For areas where the texture meets the wall, use a 6" broad knife pressed into the corner to protect the wall while repairing the defect. Allow the repaired area to dry 24-48 hours.

CLEAN-UP

Clean hands and application tools with warm soapy water.

PHYSICAL PROPERTIES

Physical Properties		READY-MIXED POPCORN CEILING PATCH
Composition		Sodium Potassium Silicate, Calcium Carbonate
Weight	Per Gallon	9.0-9.8 lbs.
Solids	By Weight	52.0-55.0%
Volatile Organic Compounds		0 g/l
Practical Coverage		Will depend on the method of application and surface type
Shelf Life		5 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.