



**READY-MIXED
STUCCO PATCH**

DESCRIPTION AND USES

Ready-Mixed Stucco Patch is a ready-to-use latex based product designed to repair cracks, chips and breaks in stucco, concrete or masonry surfaces. This product can be used on interior or exterior surfaces, above or below grade.

PERFORMANCE CHARACTERISTICS

- Ready mixed, easy to use
- Designed to repair interior and exterior surfaces
- Use to repair chips and breaks in stucco, concrete and masonry surfaces
- Completely weatherproof
- Latex based formula

PRODUCTS

SKU	Description
60584	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

Area to be patched must be clean and free of any loose particles, powdery material and scaling paint. Prepare the surface by scrubbing vigorously with a wire brush.

PRODUCT APPLICATION (cont.)

MIXING

Stir contents for 10 seconds. If material appears too stiff, add 1 teaspoon of clean water and stir thoroughly.

APPLICATION

Apply only when air, material, and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is below 85%. Apply with a putty knife, broad knife, trowel or other suitable tool, Work the material well into distressed areas, filling flush and feathering edges. Deep fills greater than 1/2" require more than one application.

If matching an existing stucco finish, allow the patch to "set" for 30 minutes and gently test the area with a finishing tool such as a stipple brush, sponge or trowel. The patch surface may be moistened with a few drops of water to aid finishing. The patch, if desired, may then be primed and painted with a good quality masonry paint.

DRY TIME

Allow the repaired area to dry for 24-48 hours. Do not apply outside if rain is likely within a 4-5 hour drying period. Do not apply when the temperature could drop below 40°F (4°C).

CLEAN-UP

Clean hand and application tools with warm soapy water.

**TECHNICAL DATA****READY-MIXED STUCCO PATCH****PHYSICAL PROPERTIES**

Physical Properties		READY-MIXED STUCCO PATCH
Composition		Calcium Carbonate, Crystalline Silica
Weight	Per Gallon	13.5-14.5 lbs.
	Per Liter	1.62-1.74 kg
Solids	By Weight	84.0-88.0%
pH		9.0-9.8
Volatile Organic Compounds		0 g/l
Shelf Life		5 years
Practical Coverage		Will depend on the method of application and surface type
Flash Point		>200°F (93°C)
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877-385-8155
www.rustoleum.com

Form: GDH-228
Rev.: 012017