



# WOOD BLEACH

## DESCRIPTION AND USES

Zinsser® Wood Bleach is designed to brighten all wood surfaces including trim, paneling, floors and furniture. It bleaches new or stripped wood to a lighter, more uniform color.

## PRODUCT

SKU	DESCRIPTION
300451	Two 8 Ounce Bottles

## PRODUCT APPLICATION

### IMPORTANT

This product is for indoor use only. Test on inconspicuous area before applying to ensure favorable results. Use eye protection and rubber gloves during use. Avoid breathing vapors. Ensure fresh air entry during application and drying.

### SURFACE PREPARATION

**ALL SURFACES:** Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with Krud Kutter® Original Cleaner Degreaser, commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry. All surfaces must be dry at time of application. Remove loosely adhered previous coatings by scraping and sanding. Remove all sanding dust and dirt with a vacuum and grease or glue with a clean rag dampened with mineral spirits.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## PRODUCT APPLICATION (cont.)

### DIRECTIONS FOR USE

Spread a solvent resistant drop cloth around the work area in case of drips or spills. Protect eyes and skin. Wear safety goggles and chemical resistant gloves. Amount of bleaching will vary with the type of wood and length of treatment time.

Use separate plastic or glass container for each solution. Do Not mix B with A solution or with any other product.

Apply Solution A with a new sponge, completely saturating the area to be bleached. Let stand 5 minutes for soft woods and 10 minutes for hard woods. While surface is still wet, use another sponge to apply Solution B over Solution A. Let stand overnight to dry.

Sand lightly to remove residue and lighten wood. If a lighter shade is desired, repeat the process.

Once desired look is achieved, the surface should be neutralized with vinegar diluted with 2 parts water.

**CAUTION!** Avoid contact with eyes and skin. If eye contact occurs, flush with water for at least 15 minutes. If irritation persists, seek medical attention. Avoid contact with the skin. Wash exposed areas with soap and water. Do not take internally. **KEEP OUT OF REACH OF CHILDREN.**

	<b>TECHNICAL DATA</b>	<b>ZNR-02</b>
	WOOD BLEACH	

**PHYSICAL PROPERTIES**

WOOD BLEACH	
<b>Composition</b>	Borax, Sodium Hydroxide, Hydrogen Peroxide
<b>Weight</b>	<b>Per-Gallon</b> 8.3 LBS
	<b>Per-Liter</b> 1.0 KG
<b>pH</b>	NA
<b>VOC (Based on Consumer Product Rule)</b>	<0.1%
<b>Shelf Life</b>	3 Years
<b>Practical Coverage</b>	Varies on wood type
<b>Flash Point</b>	>200°F (93°C)
<b>Caution</b>	<p>Contains sodium hydroxide. May cause eye irritation. Flush eyes immediately with large amounts of water for at least 15 minutes. Get medical attention. Avoid contact with skin. Wash exposed areas thoroughly with soap and water. Get medical attention. Do not swallow. If swallowed, contact a physician, poison control center, or hospital emergency room. <b>DO NOT INDUCE VOMITING.</b> Use only with adequate ventilation.</p> <p style="text-align: center;"><b>KEEP OUT OF REACH OF CHILDREN</b></p>
<b>Safety Information</b>	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.