



ZINSSER® ADHESIVE REMOVER

DESCRIPTION AND USES

Zinsser® Adhesive Remover is designed to remove hardened mastic or other adhesives that remain after old floor coverings such as tile, carpet or linoleum have been removed. The semi-paste formula clings to surfaces, acting within minutes to completely remove old adhesive prior to applying new mastic or adhesive for new floor coverings. It can also be used for removing latex adhesive, asphalt, tar, oil, wax, soot, gum and other tacky substances.

PERFORMANCE CHARACTERISTICS

- Clings to round and vertical surfaces
- Works in 10 minutes
- Excellent for wood, metal, masonry & marine

PRODUCTS

SKU	Description
42081	1-Gallon
42084	1-Quart

PRODUCT APPLICATION

SURFACE PREPARATION

Spread a solvent resistant drop cloth covered with newspapers around the work area in case of drips and spills. Protect eyes and skin. Wear safety goggles and chemical resistant gloves. Keep away from heat, sparks and flames.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-Approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRODUCT APPLICATION (cont.)

APPLICATION

USE ONLY WITH ADEQUATE VENTILATION. Apply only when air and surface temperatures are between 65-90°F (18-32°C) and the relative humidity is below 85%. Shake can before using and open can carefully to relieve pressure. Pour Zinsser Adhesive Remover into a glass or metal container. Use an inexpensive natural bristle brush to apply a heavy coat over the old adhesive. Allow to sit for 10-20 minutes for maximum penetration. The time required will vary depending on the thickness of the adhesive being removed. Remove softened adhesive with a putty knife or scraper. For best results, wash surface with Zinsser Stripper Wash before applying new adhesive.

SPILLAGE

Open containers carefully and close after each use. If spilled, contain spilled material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Clean up rags, papers and waste promptly. Allow solvent to evaporate, then dispose of in a metal container.

CLEAN-UP

Clean up tools and brushes with soap and water.



TECHNICAL DATA

ZINSSER® ADHESIVE REMOVER

PHYSICAL PROPERTIES

Physical Properties		ADHESIVE REMOVER
Composition		Methanol, Methylene Chloride, Toluene
Weight	Per Gallon	9.3 lbs.
	Per Liter	1.11 kg
Volatile Organic Compounds		298 g/l
Practical Coverage		Varies with thickness and type of coating
Shelf Life		5 years
Flash Point		>200°F (93°C)
Caution!		Cannot be made non-poisonous. Causes burns to eyes and skin, nose and throat irritation. Do not get in eyes, on skin or clothing. May be harmful if absorbed through skin. May cause allergic skin reaction. Wash thoroughly after handling. KEEP OUT OF REACH OF CHILDREN.
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.