



RENOVATOR MULCH COLOR REFRESH

DESCRIPTION AND USES

Rust-Oleum® Renovator Mulch Color Refresh is a ready-to-use formula designed to add vibrant color to mulch. Mulch Color Refresh has excellent fade resistance and adds vivid color that will last all season long. This easy to apply solution for mulch will not harm plants or vegetation. Mulch Color Refresh is designed for use on faded mulch. **EXTERIOR USE ONLY.**

FEATURES

- Adds vibrant color to mulch
- Excellent fade resistance
- Will not harm plants or vegetation

PRODUCTS

SKU	Description
307524	Mulch Red 1-Gallon
307525	Mulch Black 1-Gallon
307526	Mulch Brown 1-Gallon

PRODUCT APPLICATION

SURFACE PREPARATION

Mulch should be dry and free of all debris such as leaves and sticks prior to application. Cover and mask off surrounding areas to protect from overspray. Protective clothing and gloves are recommended.

PRECAUTIONS & TEMPERATURE SAFEGUARDS

DO NOT APPLY IF RAIN IS EXPECTED WITHIN 12 HOURS OF APPLICATION. DO NOT APPLY PRODUCT IN WET, WINDY OR DUSTY CONDITIONS. Apply when air and surface temperature is between 45°F (7°C) and 100°F (38°C) for at least 3 hours after application with the relative humidity below 85%.

PRODUCT APPLICATION (cont)

APPLICATION

ONE COAT OF RENOVATOR MULCH COLOR REFRESH IS REQUIRED. Shake well before and during use. When using more than one gallon, combine all containers to ensure color consistency. Pour the product into a standard deck or garden type sprayer. Pressurize the sprayer by pumping several times. When the sprayer is pressurized properly, the product may be sprayed. Test the product in a small space prior to the application to ensure the desired color is achieved. Place the tip of the sprayer 6-10" from mulch when spraying. For best results, and coverage, place the pump sprayer nozzle on the finest mist setting and spray in a circular pattern.

COVERAGE

Covers up to 350 square feet per gallon. One coat is required. Actual coverage will vary depending on mulch type, age and porosity. If a darker shade is desired, two coats may be applied.

DRY TIMES

Dry times are based on 70°F and 50% relative humidity. The material will dry to the touch in 30-45 minutes. Allow 4-6 hours before light foot traffic and 24 hours before placing any furniture on the mulch. Cooler temperatures or higher humidity may increase dry times.

CLEAN UP

Use mild soap and water. Clean up drips or spatters with water immediately as dried coating may be difficult to remove. When project is complete, rinse out the pump sprayer with water by pressuring the contents and empty out by way of the spray nozzle. Follow the equipment manufacturer's instructions to clean the pump sprayer.

CLOGGING

If the pump sprayer nozzle becomes clogged, remove and rinse out with water. Once the nozzle is cleaned, re-attach to the pump sprayer.

STORAGE

KEEP FROM FREEZING. CLOSE CONTAINER AFTER EACH USE TO PRESERVE THE PRODUCT.

KEEP OUT OF REACH OF CHILDREN



TECHNICAL DATA

RENOVATOR™ MULCH COLOR REFRESH

PHYSICAL PROPERTIES

		RENOVATOR MULCH COLOR REFRESH
Composition		Acrylic Copolymer
Pigment Type		Iron Oxide
Solvents		Water
Weight	Per Gallon	8.50-8.80 lbs.
	Per Liter	1.03-1.06 kg
Solids	By Weight	16.7-20.1%
	By Volume	14.6-15.7%
Volatile Organic Compounds		<50 g/l
Practical Coverage at Recommended DFT		Approximately 350 sq.ft./gal. One coat is required.
Dry Time at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	30-45 minutes
	Light Traffic	4-6 hours
	Place Furniture	24 hours
Shelf Life		2 years
Flash Point		>200°F (93°C)
Storage		KEEP FROM FREEZING
Safety Information		For additional information, see the SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.