

**RUST-OLEUM®****2300 SYSTEM****INVERTED STRIPING PAINT****DESCRIPTION AND USES**

High Performance Inverted Striping Paint is a lead-free aerosol paint that features weather and abrasion resistance for durability. When used with one of the Rust-Oleum Striping Machines, these coatings are ideal for striping parking lots and warehouse aisles. They dry fast and adhere to concrete, pavement, gravel, grass and more.

**PRODUCTS**

SKU	Description
2364838	Red
2326838	Blue
2378838	Black
2348838	Yellow
2391838	White

**PACKAGING**

20 fl. oz. container, 18 oz. fill wt., 6 aerosols packed to a carton

**PRODUCT APPLICATION****SURFACE PREPARATION**

**ALL SURFACES:** Remove loose debris and contaminants by sweeping the surface before application of the coating. Grease, oil and chemical contaminants are best removed by washing the surface with Krud Kutter® Original Cleaner Degreaser, commercial detergent, or other suitable cleaner. Rinse thoroughly with clean fresh water and allow to fully dry.

**APPLICATION**

Use when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Protect surrounding surfaces from overspray. Overspray can carry a significant distance. The Inverted Striping sprays are designed for use with Rust-Oleum Striping Machine item #2395000. Follow machine directions for proper use. The width of the stripe can be varied from 2-4 inches wide by adjusting the position of the can holder on the Striping Machine. For best results be sure the Striping Machine is in motion before squeezing the trigger and release the trigger before stopping. If clogging occurs, carefully remove spray tip and clean in thinner. **DO NOT** insert any object into can valve opening. Use care when replacing the spray tip. The inverted striping aerosols can also be used with the #2388000 Striping Wand. Properly discard empty container. Do not burn or place in trash compactor. Empty container can be recycled.



**2300 SYSTEM INVERTED STRIPING PAINT**

**PHYSICAL PROPERTIES**

		INVERTED STRIPING PAINT
<b>Resin Type</b>		Vinyl Toluene Modified Alkyd
<b>Pigment Type</b>		Varies with color
<b>Solvents</b>		Xylene and Toluene
<b>Solids</b>	<b>By Weight</b>	31-41%
	<b>By Volume</b>	—
<b>MIR</b>		Maximum value of 0.85
<b>Fill Weight</b>		18 oz. (510 g)
<b>Recommended Dry Film Thickness (DFT) Per Coat</b>		1.0-2.0 mils (25-50µ)
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>		275-300 ft. @ 3" wide using 2348838 Yellow Coverage is dependent on surface porosity
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Tack-free</b>	<10 minutes
	<b>Handle</b>	30 minutes
	<b>Recoat</b>	Anytime
<b>Dry Heat Resistance</b>		200°F (93°C)
<b>Shelf Life</b>		5 years
<b>Safety Information</b>		<b>THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. DANGER! EXTREMELY FLAMMABLE. MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. FOR INDUSTRIAL OR COMMERCIAL USE ONLY. SEE THE SAFETY DATA SHEET (SDS) AND LABEL WARNINGS FOR ADDITIONAL SAFETY INFORMATION.</b>

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.