

**RUST-OLEUM®****LEAKSEAL® FLEXIBLE SEALER****DESCRIPTION AND USES**

Rust-Oleum® LeakSeal® is an easy to use, rubberized protective utility coating designed to fill and seal leaks and cracks. It provides a water-tight, flexible seal that prevents moisture penetration and corrosion. LeakSeal dries to a semi-smooth finish that will not sag or drip, and can be top-coated with latex or oil-based paints. This product is designed for use on metal, aluminum, galvanized metal, PVC, concrete, masonry, asphalt roofing materials, vinyl siding, fiberglass, and more.

LeakSeal complies with USDA FSIS regulatory sanitation performance standards for food establishment facilities. This coating is impervious to moisture and easily cleaned and sanitized.

**PRODUCTS**

266784	Black (15 oz. fill)
267453	Clear (13.75 oz. fill)
279415	ANSI Gray (15 oz. fill)
279416	Munsell Green (15 oz. fill)

**PRODUCT APPLICATION****SURFACE PREPARATION**

Remove all dirt and debris from the area to be coated. Wash area with a detergent and water solution, rinse with fresh water, and allow the surface to dry thoroughly. Remove any loose paint or previous coatings with a wire brush or sandpaper. Lightly sand glossy surfaces. Wipe the sanded surface clean when finished.

**PRODUCT APPLICATION (cont.)****APPLICATION**

Use outdoors or in a well ventilated area such as an open garage. Apply when temperature is between 50°F and 90°F (10-32°C) and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 200°F (93°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. A test spray on cardboard is recommended to obtain a feel for the spray pattern. Hold can 8-18" from the surface and spray in short even strokes. It is recommended to apply a light first coat. Apply a second heavier coat to ensure proper coverage. A thicker film can be achieved by moving the nozzle closer to the surface. Initial spray may have some foaming or bubbling, but will dissipate as the coating dries. For best results, apply 2 coats. Allow to dry 15-30 minutes between coats.

LeakSeal can be top-coated with water-based or oil-based paints after 24 hours.

**DRY & RECOAT**

Dry and recoat times are based on 70°F and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 20-30 minutes, to handle in 45-60 minutes, and can be re-coated with itself in 20-30 minutes. Allow 24 hours for full cure.

**CLEAN-UP**

Wipe off tip when finished. Clean-up wet paint with xylene or mineral spirits. Properly discard empty container. Do not burn or place in home trash compactor.

**CLOGGING**

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.



**PHYSICAL PROPERTIES**

<b>Resin Type</b>	Hydrocarbon	
<b>Solvents</b>	Naphtha and Xylene	
<b>MIR</b>	1.20 Max	
<b>Fill Weight</b>	15 ounces	
<b>Recommended Dry Film Thickness</b>	2.5 mils (62.5µ)	
<b>Practical Coverage at Recommended DFT (assumes 15% material loss)</b>	8.0 sq.ft./can (0.74 m <sup>2</sup> /can)	
<b>Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity</b>	<b>Tack-free</b>	20-30 minutes
	<b>Handle</b>	45-60 minutes
	<b>Recoat (with itself)</b>	20-30 minutes
	<b>Topcoat</b>	24 hours
<b>Shelf Life</b>	2-3 years	
<b>Safety Information</b>	For additional information, see SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.