# **TECHNICAL DATA**



# **3500 SYSTEM CLEANER/DEGREASER**

## **DESCRIPTION AND USES**

A heavy-duty non-abrasive cleaner/degreaser that handles the toughest cleaning jobs in industry.

Ideal for use on painted, unpainted and rusted steel surfaces, as well as stainless steel, aluminum, concrete, tile, glass and most plastics. (Conduct a test application on plastics before use.) This product is excellent for removing accumulated grime, smudges, smoke, spills, stains, cutting fluids, diesel oil, adhesive gum, food products and foreign material. 3599 Cleaner/Degreaser is also extremely effective in preparing surfaces prior to painting. Use on walls, floors, machinery and equipment.

NOTE: 3599 is not recommended for use on styrene plastics.

### APPEARANCE

Undiluted, clear amber liquid. Diluted in water, clear milky liquid.

#### PRODUCTS

SKU #	Description
3599507	1 quart bottle
3599402	1 gallon bottle
3599300	5 gallon pail
3599100	55 gallon drum
3599838	14 ounce aerosol

### **PRODUCTS APPLICATION**

#### **DIRECTIONS FOR USE (APPLICATIONS)**

Apply Industrial Pure Strength<sup>®</sup> 3599 Cleaner/Degreaser directly on surfaces to be cleaned. Rub with cloth or scrub with stiff bristled brush and rinse thoroughly with fresh water.

DIP TANKS: Use full strength to remove the most difficult grease and oils from engine parts and equipment.

FLOORS AND WALLS: Dilute using 3-4 ounces 3599 Cleaner/Degreaser to one gallon water. (1:40 dilution ratio). To strip floors of wax and dirt build-up, dilute using 4 ounces 3599 Cleaner/Degreaser to one gallon of hot water. (1:30 dilution ratio)

HEAVILY SOILED FLOORS: Scrape away excess dirt, grease and oil. Apply at full strength for removal of most difficult dirt loads. For lesser loads, dilute using one pint 3599 Cleaner/Degreaser in one gallon fresh water. Apply and allow to stand 10-15 minutes. Scrub with stiff bristled brush if necessary. Rinse with fresh water.

# DIRECTIONS FOR USE (GENERAL PURPOSE CLEANING)

Tile, grout, aluminum, brass, copper, bronze, stainless steel, fiberglass, mirrors and windows:

Dilute using 1 oz. 3599 Cleaner/Degreaser to one half gallon water. (1:64 dilution) or as low as 1 ounce. of Cleaner/Degreaser to one gallon of water (1:128 dilution ratio).



**TECHNICAL DATA** 

# **3500 SYSTEM CLEANER/DEGREASER**

#### PHYSICAL PROPERTIES

		CLEANER/DEGREASER	
Composition		Terpene and Nonionic Surfactant Mix	
Pigment Type		NA	
Weight	Per Gallon	7.2 lbs.	
	Per Liter	0.86 kg	
рН		7.5-8.5	
VOC (Concentrate)		20%	
Safety Information		For additional information, see SDS	

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061 An RPM Company

Phone: 877•385•8155 www.rustoleum.com/industrial