



DECKSTRIP® ASR ACRYLIC STAIN REMOVER

DESCRIPTION AND USES

Wolman® DeckStrip® ASR Acrylic Stain Remover is a ready-to-use, premium quality, exterior wood stripper for all types of acrylic deck and siding stains. In just 15 minutes, DeckStrip ASR will cut through and remove relatively new or weathered acrylic/latex solid and semi-solid stains, including those labeled 100% acrylic. With the aid of a highly concentrated formula, special wetting agents and a thickener for vertical surfaces, tough-to-remove acrylics are quickly dissolved and easily rinsed away with a pressure-washer – no scraping or sanding required. Once stripped, wood is restored to its bright, clean, natural look. Using DeckStrip ASR before re-application of a protective finish or stain ensures its proper adhesion, penetration and optimum performance.

FEATURES

- Spray on, pressure wash away
- No scraping or sanding
- Clings to vertical surfaces for one application stripping
- Biodegradable

PRODUCT

SKU	DESCRIPTION
14706	1 Gallon

RECOMMENDED USES

FOR EXTERIOR USE ONLY

Use DeckStrip ASR to strip and restore outdoor wood decks, fences, siding, shakes and shingles, boat docks & boardwalks, outdoor furniture & décor, gazebos & arbors, play sets and more.

WOOD TYPES: Use on all wood types, including pressure treated lumber, Cedar, Redwood, exotic hardwoods (Mahogany, Ipé, Teak, etc.), and North American hardwoods.

Note: To strip traditional oil or solvent-based deck stains, semi-transparent stains, toners, tinted wood protectors or sealers, select Wolman DeckStrip Stain & Finish Remover and use according to label directions.

PRODUCT APPLICATION

Before You Start: Make sure entire wood surface is dry and free of dust, dirt and debris. If the surface is hot to the touch or in direct sunlight, dampen with fresh water to cool. Apply when outside temperatures are above 40°F. Pre-rinse grass, plants and shrubs surrounding the wood structure to be stripped, and then cover foliage to protect it from exposure to the product. Mask off siding and cover all wood surfaces not intended to be stripped. Cover any exposed aluminum surfaces (siding and flashing) to prevent corrosion. Protect adjacent concrete surfaces from rinse water. Sweep away surface dirt and debris. Remove any standing water before beginning application.

Weather Conditions:

For best results, apply when outside temperature is above 50°F (10°C), and when 24 hours of precipitation-free weather is expected. Surface to be stripped should be out of direct sunlight to avoid premature evaporation of the product.

Safe Handling directions must be followed to avoid exposure to over-spray. (See Handling and Storage section)

CAUTION: Bare wood and/or coated surfaces can become slippery when wet. Use caution when walking on wet surfaces.

Prepare to Use:

Moderately shake container, then pour into sprayer tank. If using a brush or mop, pour product into a 2-½ gallon plastic bucket. Do not mix with any other products.

Apply:

A synthetic bristle brush or mop, pump sprayer or airless sprayer (with no aluminum parts) is recommended. When working on vertical surfaces start at the bottom and work to the top of the structure.

Working on 20 square feet at a time to maintain optimum surface wetness, apply product and let sit for 15 minutes. If stripper dries prematurely, keep it wet with additional product as needed.



DECKSTRIP® ASR

ACRYLIC STAIN REMOVER

PRODUCT APPLICATION (cont.)

Rinse Pressure Wash:

Pressure wash using a 40° tip and 1,500-2,500 psi to prepare pressure-treated wood and hardwood. Use 500-1,000 psi to prepare Cedar and Redwood. Move lengthwise with boards to avoid cut marks across grain.

Repeat steps until entire surface has been stripped. When finished, rinse surrounding grass and plants thoroughly.

Rinse Brush and Hose:

If pressure washing cannot be employed, vigorously scrub surface with a stiff, synthetic, short-bristle broom or brush for several minutes using moderate pressure. After brushing, rinse thoroughly with a garden hose, using the highest pressure nozzle setting available. On a vertical surface, continually rinse stripped areas to avoid streaking. Rinse any wood fibers off surrounding surfaces immediately. When dry, surface should appear clean, bright and free of previous coating.

Repeat steps until entire surface has been stripped. When finished, rinse surrounding grass and plants thoroughly.

Note: After stripping Cedar, Redwood or exotic hardwoods, black tannin stains may rise to the surface and give wood an overall darkened appearance. If this occurs, treat affected areas with Wolman Deck & Fence Brightener liquid concentrate to restore the natural wood color. DeckStrip ASR is not designed to remove tannin bleed stains.

HANDLING AND STORAGE

Clean Up:

Clean tools and equipment immediately after use with soap and water. Use water or vinegar-soaked rag to wipe off any drips or spills on unintended surfaces immediately.

Safe Handling:

During preparation and application, wear rubber or plastic coated gloves and safety goggles. If applying with a sprayer, wear a NIOSH-approved full-face respirator with an organic vapor cartridge and N-95 pre-filter. Care should be taken to cover any exposed aluminum surfaces to prevent discoloration, as this product is corrosive to metal.

DO NOT MIX WITH ANY OTHER PRODUCTS, especially those containing chlorine or bleach (sodium hypochlorite). Rinse grass and plants with water after exposure.

PRECAUTIONS

Precautions:

DANGER! MAY BE FATAL IF SWALLOWED. CAUSES SEVERE BURNS. CONTAINS SODIUM HYDROXIDE. May be harmful if swallowed. Causes eye and skin irritation. Prevent contact with eyes and skin. During preparation and application, wear rubber or PVC gloves and safety goggles. Wash thoroughly after handling. May cause respiratory and throat irritation. Do not breathe spray mist. If applying with a sprayer, wear a properly fitted, NIOSH approved respirator. Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.



**DECKSTRIP® ASR
ACRYLIC STAIN REMOVER**

PHYSICAL PROPERTIES

		ACRYLIC STAIN REMOVER
Active Ingredient		Sodium Hydroxide
Pigment Type		NA
Solvents		Ethylene Glycol Monobutyl Ether, Propylene Glycol, Water
Weight	Per Gallon	8.7 lbs.
	Per Liter	1.0 kg
Volatile Organic Compounds		<1 g/l
pH		13 minimum
Practical Coverage		One (1) gallon will cover approximately 150 sq.ft. depending on the coating type, number of layers, surface porosity and method of application
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity		Allow wood to dry thoroughly before applying a water-based stain or finish. Allow a minimum of 24 hours before applying an oil-based stain or finish.
Shelf Life		2 years
Flash Point		>200°F
Safety Information		For additional information, see SDS

Calculated values are shown and may vary from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.